

PC® FABRIC 79 PRODUCT DATA SHEET

IMPORTANT: MATERIAL SAFETY DATA SHEETS ARE AVAILABLE AND SHOULD BE READ BEFORE USING THIS PRODUCT.

DESCRIPTION:

PC® Fabric 79 is an open mesh, synthetic fabric for reinforcing PITTCOTE® 404 (FI-138) or PITTCOTE® 300 (FI-120) coating over FOAMGLAS® insulation. The large mesh openings allow the coating to easily penetrate and bond to the insulation and fabric. The thickness of the fabric assures that the proper thickness of the coating is applied and gives the required strength. The high elongation accommodates large and mechanical movements without rupture and allows maximum movement of the coating.

*TYPICAL PROPERTIES:

| PROPERTY | |
|--|--------------------------------|
| Composition: | 100% polyester |
| Weight g/m ² , (oz/yd ²): | 94.3 ± 14.2 (2.78 ± 0.42) |
| Meshes per cm (per in.): | 2.4 (6 x 5.5) |
| Mesh Opening, mm (in): | 3.18 (0.125) |
| Thickness, mm (inches): | 0.67 ± 0.13 (0.026 ± 0.005) |
| Ball Burst min. kg/cm ² (psi): | 7.0 (100) |
| Width, in (m): | 1 (39-40) |
| Length, m (yd): | 45.7 (50) |
| Weight/Roll, kg, (lbs): | 3.9 ± 0.6 (8.7 ± 1.3) |
| Fire Resistance: | Combustible |

*Typical properties at time of printing, subject to change. Consult Pittsburgh Corning Corporation.

APPLICATION:

PC® Fabric 79 is cut to fit piping, vessel or shape, allowing a minimum of 5 to 8cm (2 to 3 in.) overlap at all seams. Fabric should be cut to fit closely without wrinkles. Scissors or shears are recommended for cutting. Apply a tack coat of PITTCOTE® 404 coating or PITTCOTE® 300 finish to FOAMGLAS® insulation according to the recommendations. Immediately smooth the Fabric into the coating so it is free of wrinkles. Additional coating is applied according to the specific product data sheet being referenced.

FABRIC SHOULD NOT SHOW THROUGH THE SECOND APPLICATION OF WET COATING BUT THE OUTLINE OF FABRIC WILL BE VISIBLE IN DRIED COATING.

When used with PITTCOTE® 404 coating, the tack coat can be sprayed through the fabric and worked with a squeegee. This saves labor and makes the operation cleaner. The second coat is applied after the tack coat takes its initial set.

LIMITATIONS:

Keep fabric stored in a dry location.

PACKAGING:

Fiberboard box

The information contained herein is accurate and reliable to the best of our knowledge. But, because Pittsburgh Corning Corporation has no control over installation workmanship, accessory materials or conditions of application, NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, IS MADE as to the performance of an *installation* containing Pittsburgh Corning products. In no event shall Pittsburgh Corning be liable for any damages arising because of product failure, whether incidental, special, consequential or punitive, regardless of the theory of liability upon which any such damages are claimed. Pittsburgh Corning Corporation provides written warranties for many of its products, and such warranties take precedence over the statements contained herein.

FOAMGLAS®, PC® and PITTCOTE® are federally registered trademark owned by Pittsburgh Corning Corporation

Pittsburgh Corning Corporation
800 Presque Isle Drive Pittsburgh, PA 15239-2799 USA
Toll Free: 800-545-5001
Phone: (724)327-6100 Fax: (724)387-3806
<http://www.foamglas.com/>

Pittsburgh Corning Europe S.A./ N.V.
(EMEA Headquarters)
Albertkade 1
3980 Tessenderlo
Belgium
Phone: +32-13-611-415 Fax: +32-13-351-567